


## TagX BUT BLE

### Bluetooth Low Energy asset tag

#### Data sheet



#### Key features

- Suitable for outdoor and industrial applications
- Based on Nordic nRF52832
- Simultaneous support of iBeacon and Eddystone
- 3-axis accelerometer for motion detection
- Call button and 2x LEDs
- IP67 enclosure with flanges for flexible fastening
- Powered by replaceable CR2477 lithium battery

#### GATT and advertising

Full support for specifications Eddystone Configuration GATT Service by Google

Up to 4 slots configurable for Eddystone frame types: UID, URL, TLM, EID

Up to 4 slots configurable for the following frame types: iBeacon, Quuppa (emulation mode), Sensors

TX power	-40, -20 to 4 dBm (with 4 dB steps). Programmable for each slot
Advertising interval	0.1 to 60 secs. Programmable for each slot
Global configuration options	non-connectable mode, anonymous mode, programmable time period, locked/unlocked mode, change password
Firmware update	OTA (Over-the-Air) firmware update

#### Device specifications

##### Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
MCU core	ARM Cortex-M4 32-bit CPU
Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA

##### Radio specifications

Standard	Bluetooth 4.2 Bluetooth Low Energy (compatible with BLE 5.x)
Frequency band	2.402 to 2.480 GHz (according to Bluetooth 4.0 specifications)
Advertising channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz) (according to Bluetooth 4.0 specifications)
Channel spacing	2 MHz (according to Bluetooth 4.0 specifications)
TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)



BlueUp S.r.l.  
Loc. Belvedere, Ingresso 2, 53034 Colle di Val d'Elsa (SI) - ITALY  
Tel. +39 0577 043101 / +39 344 2030929, Fax +39 0577 043101  
E-mail: [info@blueupbeacons.com](mailto:info@blueupbeacons.com), Web: [www.blueupbeacons.com](http://www.blueupbeacons.com)  
P.IVA/CF/N. iscr. CCIAA (SI). 01373980521, VAT n.: IT01373980521

<b>Antenna</b>	
Type	Integrated meandered planar inverted F-antenna (PIFA)
Gain	2 dB (max)
Radiation diagram	Omnidirectional
<b>Power</b>	
Power supply	Battery
Replaceable	Yes
Type	CR2477 (3V, lithium)
Model	Panasonic Industrial CR2477 (typical capacity 1000 mAh @ 25°C)
<b>Sensors and interfaces</b>	
Sensors	3-axis MEMS linear accelerometer Button
Interfaces	2x LEDs (yellow, red)
<b>Mechanical specifications</b>	
Material	ABS plastic
Color	White
Size	77 x 46 x 16 mm (including flanges)
Weight	27 gr
Fastening	Screws (max. M3.5), cable-ties
Opening	Back lid with four screws
Protection	IP67/NEMA6
Flammability	UL 94 HB
<b>Environmental specifications</b>	
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under 0°C)
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)
<b>Certifications</b>	
CE, FCC	

BlueUp reserves the right to change product specifications at any time without prior notice.  
Bluetooth is a trademark of Bluetooth SIG, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc., Qu-  
uppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.