


## TagX BLE

### Bluetooth Low Energy asset tag

### Data sheet



#### Key features

- Suitable for outdoor and industrial applications
- Based on Nordic nRF52832
- Simultaneous support of iBeacon and Eddystone
- 3-axis accelerometer for motion detection
- IP67 enclosure
- Flanges for flexible fastening options
- Powered by replaceable CR2477 lithium battery

#### GATT and advertising

Full support for specifications Eddystone Configuration GATT Service by Google

Up to 4 slots configurable for Eddystone frame types: UID, URL, TLM, EID

Up to 4 slots configurable for the following frame types: iBeacon, Quuppa (emulation mode), Sensors

TX power	-40, -20 to 4 dBm (with 4 dB steps). Programmable for each slot
----------	---

Advertising interval	0.1 to 60 secs. Programmable for each slot
----------------------	--

Global configuration options	non-connectable mode, anonymous mode, programmable time period, locked/unlocked mode, change password
------------------------------	---

Firmware update	OTA (Over-the-Air) firmware update
-----------------	------------------------------------

#### Device specifications

##### Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
-------------	---

MCU core	ARM Cortex-M4 32-bit CPU
----------	--------------------------

Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA
----------------------------	---

##### Radio specifications

Standard	Bluetooth 4.2 Bluetooth Low Energy (compatible with BLE 5.x)
----------	--

Frequency band	2.402 to 2.480 GHz (according to Bluetooth 4.0 specifications)
----------------	---

Advertising channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz) (according to Bluetooth 4.0 specifications)
----------------------	---

Channel spacing	2 MHz (according to Bluetooth 4.0 specifications)
-----------------	---

TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)
----------	---



BlueUp S.r.l.  
Loc. Belvedere, Ingresso 2, 53034 Colle di Val d'Elsa (SI) - ITALY  
Tel. +39 0577 043101 / +39 344 2030929, Fax +39 0577 043101  
E-mail: [info@blueupbeacons.com](mailto:info@blueupbeacons.com), Web: [www.blueupbeacons.com](http://www.blueupbeacons.com)  
P.IVA/CF/N. iscr. CCIAA (SI). 01373980521, VAT n.: IT01373980521

<b>Antenna</b>	
Type	Integrated meandered planar inverted F-antenna (PIFA)
Gain	2 dB (max)
Radiation diagram	Omnidirectional
<b>Power</b>	
Power supply	Battery
Replaceable	Yes
Type	CR2477 (3V, lithium)
Model	Panasonic Industrial CR2477 (typical capacity 1000 mAh @ 25°C)
<b>Sensors and interfaces</b>	
Sensors	3-axis MEMS linear accelerometer
Interfaces	2x LEDs (yellow, red)
<b>Mechanical specifications</b>	
Material	ABS plastic
Color	White
Size	77 x 46 x 16 mm (including flanges)
Weight	27 gr
Fastening	Screws (max. M3.5), cable-ties
Opening	Back lid with four screws
Protection	IP67/NEMA6
Flammability	UL 94 HB
<b>Environmental specifications</b>	
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under 0°C)
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)
<b>Certifications</b>	
CE, FCC	

BlueUp reserves the right to change product specifications at any time without prior notice.  
Bluetooth is a trademark of Bluetooth SIG, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc., Qu-  
uppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.