




# USB BLE

## Bluetooth Low Energy USB-dongle beacon

### Data sheet







### Key features

- Suitable for integration with PoS, PCs, embedded devices
- Indoor proximity detection
- Based on Nordic nRF52832
- Simultaneous support of iBeacon and Eddystone
- Powered by any USB port or AC/DC power-supply with USB output

### GATT and advertising

Full support for specifications Eddystone Configuration GATT Service by Google	
Up to 4 slots configurable for Eddystone frame types: UID, URL, TLM, EID	
Up to 4 slots configurable for the following frame types: iBeacon, Quuppa (emulation mode), Sensors	
TX power	-40, -20 to 4 dBm (with 4 dB steps). Programmable for each slot
Advertising interval	0.1 to 60 secs. Programmable for each slot
Global configuration options	non-connectable mode, anonymous mode, programmable time period, locked/unlocked mode, change password
Firmware update	OTA (Over-the-Air) firmware update

### Device specifications

#### Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
MCU core	ARM Cortex-M4 32-bit CPU
Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA

#### Radio specifications

Standard	Bluetooth 4.2 Bluetooth Low Energy (compatible with BLE 5.x)
Frequency band	2.402 to 2.480 GHz (according to Bluetooth 4.0 specifications)
Advertising channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz) (according to Bluetooth 4.0 specifications)
Channel spacing	2 MHz (according to Bluetooth 4.0 specifications)
TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +1 dBm (max)



<b>Antenna</b>	
Type	Integrated meandered planar inverted F-antenna (PIFA)
Gain	-3 dB (max)
Radiation diagram	Omnidirectional
<b>Power</b>	
Power supply	USB-A
Voltage	5V
<b>Sensors and interfaces</b>	
Sensors	-
Interfaces	-
<b>Mechanical specifications</b>	
Material	ABS plastic
Color	Black
Size	18 x 13 x 6 mm
Weight	2 gr
Protection	IP40
Flammability	UL 94 HB
<b>Environmental specifications</b>	
Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +60°C
<b>Certifications</b>	
CE	

BlueUp reserves the right to change product specifications at any time without prior notice.

Bluetooth is a trademark of Bluetooth SIG, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc.,  
Quuppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.