


## Ultra BLE

Bluetooth Low Energy high-end beacon with optional sensors


### Data sheet



#### Key features

- Suitable for indoor localization and tracking
- Based on Nordic nRF52832
- Simultaneous support of iBeacon and Eddystone
- Directive antenna for higher accuracy
- Enclosure suitable for wall/ceiling installation
- Optional versions with environmental sensors
- Powered by 4x alkaline batteries or USB

Works with  
Apple iBeacon


Eddystone

#### GATT and advertising

Full support for specifications Eddystone Configuration GATT Service by Google	
Up to 4 slots configurable for Eddystone frame types: UID, URL, TLM, EID	
Up to 4 slots configurable for the following frame types: iBeacon, Quuppa (emulation mode), Sensors	
TX power	-40, -20 to 4 dBm (with 4 dB steps). Programmable for each slot
Advertising interval	0.1 to 60 secs. Programmable for each slot
Global configuration options	non-connectable mode, anonymous mode, programmable time period, locked/unlocked mode, change password
Firmware update	OTA (Over-the-Air) firmware update

#### Device specifications

##### Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
MCU core	ARM Cortex-M4 32-bit CPU
Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA

##### Radio specifications

Standard	Bluetooth 4.2 Bluetooth Low Energy (compatible with BLE 5.x)
Frequency band	2.402 to 2.480 GHz (according to Bluetooth 4.0 specifications)
Advertising channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz) (according to Bluetooth 4.0 specifications)
Channel spacing	2 MHz (according to Bluetooth 4.0 specifications)
TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)



<b>Antenna</b>				
Type	Directive planar printed antenna			
Gain	5 dB (max)			
Radiation diagram	Directive with 10dB front-to-back ratio (FBR)			
<b>Power</b>				
Version	ZERO	BASE	PLUS	DELUXE
Power supply	Battery	Battery and external 5Vdc		
Replaceable battery	Yes			
Battery type	4x AA (1.5V, alkaline)			
Model	Panasonic LR6 or equivalent (typical tot. capacity 5600 mAh @ 25°C)			
External supply		MicroUSB port (5Vdc)		
<b>Sensors and interfaces</b>				
Version	ZERO	BASE	PLUS	DELUXE
Sensors	-	-	Temperature Humidity	Temperature Humidity Pressure CO2
Interfaces	-	Button, LED		
<b>Sensors specifications</b>				
Temperature	±0.2°C (0-70°C), ±0.3°C (-40-100°C)			
Humidity	3%RH (RH=0 to 85%RH), 4%RH (RH=85 to 95%RH),			
Pressure	±9Pa (900-1100hPa, 25-40°C), ±50Pa (300-1100hPa, 0-65°C)			
CO2	±40 ppm +5% (400 to 5000 ppm); range: 400 to 32768 ppm			
<b>Mechanical specifications</b>				
Material	ABS plastic			
Color	White			
Size	100 x 100 x 35 mm (without flanges) 124 x 100 x 35 mm (including flanges)			
Weight	197 gr			
Fastening	Lateral flanges for 2x M4 screws (optional plastic holder available)			
Opening	4 screws on back panel			
Protection	IP40 (Ver. Zero); - (other versions)			
Flammability	UL 94 V0			
<b>Environmental specifications</b>				
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under -10°C)			
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)			
<b>Certifications</b>				
CE				

BlueUp reserves the right to change product specifications at any time without prior notice.  
 Bluetooth is a trademark of Bluetooth SIG, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc., Qu-  
 oppa is a trademark of Quoppa Oy, ARM and Cortex are trademarks of ARM Inc.