

Ultra BLE

Bluetooth Low Energy high-end beacon with optional sensors

Data sheet



Key features

- Suitable for indoor localization and tracking
- Based on Nordic nRF52832
- Simultaneous support of iBeacon and Eddystone
- Directive antenna for higher accuracy
- Enclosure suitable for wall/ceiling installation
- Optional versions with environmental sensors
- Powered by 4x alkaline batteries or USB

GATT and advertising

Full support for specifications Eddystone Configuration GATT Service by Google

Up to 4 slots configurable for Eddystone frame types: UID, URL, TLM, EID

Up to 4 slots configurable for the following frame types: iBeacon, Quuppa (emulation mode), Sensors

TX power	-40, -20 to 4 dBm (with 4 dB steps). Programmable for each slot
----------	---

Advertising interval	0.1 to 60 secs. Programmable for each slot
----------------------	--

Global configuration options	non-connectable mode, anonymous mode, programmable time period, locked/unlocked mode, change password
------------------------------	---

Firmware update	OTA (Over-the-Air) firmware update
-----------------	------------------------------------

Device specifications

Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
-------------	---

MCU core	ARM Cortex-M4 32-bit CPU
----------	--------------------------

Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA
----------------------------	---

Radio specifications

Standard	Bluetooth 4.2 Bluetooth Low Energy (compatible with BLE 5.x)
----------	--

Frequency band	2.402 to 2.480 GHz (according to Bluetooth 4.0 specifications)
----------------	---

Advertising channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz) (according to Bluetooth 4.0 specifications)
----------------------	---

Channel spacing	2 MHz (according to Bluetooth 4.0 specifications)
-----------------	---

TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)
----------	---



BlueUp S.r.l.
 Loc. Belvedere, Ingresso 2, 53034 Colle di Val d'Elsa (SI) - ITALY
 Tel. +39 0577 043101 / +39 344 2030929, Fax +39 0577 043101
 E-mail: info@blueupbeacons.com, Web: www.blueupbeacons.com
 P.IVA/CF/N. iscr. CCIAA (SI). 01373980521, VAT n.: IT01373980521

Antenna				
Type	Directive planar printed antenna			
Gain	5 dB (max)			
Radiation diagram	Directive with 10dB front-to-back ratio (FBR)			
Power				
Version	ZERO	BASE	PLUS	DELUXE
Power supply	Battery	Battery and external 5Vdc		
Replaceable battery	Yes			
Battery type	4x AA (1.5V, alkaline)			
Model	Panasonic LR6 or equivalent (typical tot. capacity 5600 mAh @ 25°C)			
External supply		MicroUSB port (5Vdc)		
Sensors and interfaces				
Version	ZERO	BASE	PLUS	DELUXE
Sensors	-	-	Temperature Humidity	Temperature Humidity Pressure CO2
Interfaces	-	Button, LED		
Sensors specifications				
Temperature	±0.2°C (0-70°C), ±0.3°C (-40-100°C)			
Humidity	3%RH (RH=0 to 85%RH), 4%RH (RH=85 to 95%RH),			
Pressure	±9Pa (900-1100hPa, 25-40°C), ±50Pa (300-1100hPa, 0-65°C)			
CO2	±40 ppm +5% (400 to 5000 ppm); range: 400 to 32768 ppm			
Mechanical specifications				
Material	ABS plastic			
Color	White			
Size	100 x 100 x 28 mm (without flanges) 124 x 100 x 28 mm (including flanges)			
Weight	197 gr			
Fastening	Lateral flanges for 2x M4 screws (optional plastic holder available)			
Opening	4 screws on back panel			
Protection	IP40 (Ver. Zero); - (other versions)			
Flammability	UL 94 V0			
Environmental specifications				
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under -10°C)			
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)			
Certifications				
CE				

BlueUp reserves the right to change product specifications at any time without prior notice.
 Bluetooth is a trademark of Bluetooth SIG, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc., Qu-
 uppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.