

Card BLE

Bluetooth Low Energy wearable tag

Data sheet



Key features

- Suitable for people or asset location
- Based on Nordic nRF52832
- Simultaneous support of iBeacon and Eddystone
- 3-axis accelerometer for motion detection
- Call button
- Smart-card form factor with IP67 rating
- Powered by thin lithium battery




GATT and advertising

Full support for specifications Eddystone Configuration GATT Service by Google	
Up to 4 slots configurable for Eddystone frame types: UID, URL, TLM, EID	
Up to 4 slots configurable for the following frame types: iBeacon, Quuppa (emulation mode), Sensors	
TX power	-40, -20 to 4 dBm (with 4 dB steps). Programmable for each slot
Advertising interval	0.1 to 60 secs. Programmable for each slot
Global configuration options	non-connectable mode, anonymous mode, programmable time period, locked/unlocked mode, change password
Firmware update	OTA (Over-the-Air) firmware update

Device specifications

Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
MCU core	ARM Cortex-M4 32-bit CPU
Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA

Radio specifications

Standard	Bluetooth 4.2 Bluetooth Low Energy (compatible with BLE 5.x)
Frequency band	2.402 to 2.480 GHz (according to Bluetooth 4.0 specifications)
Advertising channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz) (according to Bluetooth 4.0 specifications)
Channel spacing	2 MHz (according to Bluetooth 4.0 specifications)
TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)



Antenna	
Type	Integrated meandered planar inverted F-antenna (PIFA)
Gain	2 dB (max)
Radiation diagram	Omnidirectional
Power	
Power supply	Battery
Replaceable	No
Type	1x CP224147 (3V, lithium)
Model	HCB CP224147 (typical capacity 800 mAh @ 25°C)
Sensors and interfaces	
Sensors	Button, 3-axis MEMS linear accelerometer
Interfaces	2 LEDs (yellow, green)
Mechanical specifications	
Material	ABS plastic
Color	White
Size	85 x 56 x 4.5 mm
Weight	15 gr
Fastening	Eyelet for lanyard or screw, dual adhesive
Opening	Ultrasonic welded
Protection	IP67/NEMA6
Flammability	UL 94 HB
Environmental specifications	
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under -10°C)
Storage temperature	10°C to +35°C
Certifications	
CE, FCC	

BlueUp reserves the right to change product specifications at any time without prior notice.

Bluetooth is a trademark of Bluetooth SIG, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc.,
Quuppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.