

SafeX Lite BLE

Bluetooth Low Energy wearable tag with alarm button

Data sheet



Key features

- Suitable for people tracking and safety
- Based on Nordic nRF52832
- Simultaneous support of iBeacon and Eddystone
- 3-axis accelerometer for motion detection
- Button, 2x LEDs, with optional vibration and buzzer
- Eyelet for lanyard or clip
- Powered by replaceable CR2477 lithium battery

GATT and advertising

Full support for specifications Eddystone Configuration GATT Service by Google

Up to 4 slots configurable for Eddystone frame types: UID, URL, TLM, EID

Up to 4 slots configurable for the following frame types: iBeacon, Quuppa (emulation mode), Safety

TX power	-40, -20 to 4 dBm (with 4 dB steps). Programmable for each slot
----------	---

Advertising interval	0.1 to 60 secs. Programmable for each slot
----------------------	--

Global configuration options	non-connectable mode, anonymous mode, programmable time period, locked/unlocked mode, change password
------------------------------	---

Firmware update	OTA (Over-the-Air) firmware update
-----------------	------------------------------------

Device specifications

Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
-------------	---

MCU core	ARM Cortex-M4 32-bit CPU
----------	--------------------------

Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA
----------------------------	---

Radio specifications

Standard	Bluetooth 4.2 Bluetooth Low Energy (compatible with BLE 5.x)
----------	--

Frequency band	2.402 to 2.480 GHz (according to Bluetooth 4.0 specifications)
----------------	---

Advertising channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz) (according to Bluetooth 4.0 specifications)
----------------------	---

Channel spacing	2 MHz (according to Bluetooth 4.0 specifications)
-----------------	---

TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)
----------	---



BlueUp S.r.l.
Loc. Belvedere, Ingresso 2, 53034 Colle di Val d'Elsa (SI) - ITALY
Tel. +39 0577 043101 / +39 344 2030929, Fax +39 0577 043101
E-mail: info@blueupbeacons.com, Web: www.blueupbeacons.com
P.IVA/CF/N. iscr. CCIAA (SI). 01373980521, VAT n.: IT01373980521

Antenna		
Type	Integrated meandered planar inverted F-antenna (PIFA)	
Gain	2 dB (max)	
Radiation diagram	Omnidirectional	
Power		
Power supply	Battery	
Replaceable	Yes	
Type	CR2477 (3V, lithium)	
Model	Panasonic Industrial CR2477 (typical capacity 1000 mAh @ 25°C)	
Sensors and interfaces		
Version	Base	Standard
Sensors	3-axis MEMS linear accelerometer, alarm button	
Interfaces	2x LEDs (yellow, red)	2x LEDs (yellow, red), buzzer, vibration
Mechanical specifications		
Material	ABS plastic	
Color	White	
Size	55 x 45 x 16 mm (case-body only) 64 x 45 x 16 mm (including flange with eyelet)	
Weight	23 gr	
Fastening	Eyelet for lanyard or clip	
Opening	Back lid with four M2.5 screws	
Protection	-	
Flammability	UL 94 HB	
Environmental specifications		
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under 0°C)	
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)	
Certifications		
CE (RED), FCC		

BlueUp reserves the right to change product specifications at any time without prior notice.
Bluetooth is a trademark of Bluetooth SIG, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc., Quuppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.