

TagX Wirepas

Wirepas Mesh 2.4GHz asset tag

Data sheet



 Wirepas

Key features

- Suitable for outdoor and industrial applications
- Based on Nordic nRF52832
- Firmware based on Wirepas libraries
- 3-axis accelerometer for motion detection
- IP67 enclosure
- Flanges for flexible fastening options
- Powered by replaceable CR2477 lithium battery

Wirepas Specifications

Based on Wirepas Mesh 2.4GHz stack v5.x

Available applications: Wirepas PosApp, BlueUp PosApp

Wirepas PosApp

Operating modes	Opportunistic anchor, NRLS tag, Autoscan tag, DA tag
BLE beaconing	iBeacon, Eddystone UID, Eddystone URL (fixed packet)

BlueUp PosApp

Configuration and diagnostics	MeshCube, Wirepas API, Wirepas NMS
Operating modes	NRLS tag, Autoscan tag (configurable for each state)
Tag states	Default, Motion, Alarm, Sleep
Positioning interval and timeout	15 secs to 18 hours (configurable for each state)
BLE beaconing	iBeacon, Safety, Quuppa Emulation (configurable for each state)

Device specifications

Electrical specifications

Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
MCU core	ARM Cortex-M4 32-bit CPU
Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA



BlueUp S.r.l.
Loc. Belvedere, Ingresso 2, 53034 Colle di Val d'Elsa (SI) - ITALY
Tel. +39 0577 043101 / +39 344 2030929, Fax +39 0577 043101
E-mail: info@blueupbeacons.com, Web: www.blueupbeacons.com
P.IVA/CF/N. iscr. CCIAA (SI). 01373980521, VAT n.: IT01373980521

Radio specifications	
Standard	Wirepas Mesh 2.4GHz (stack v5.x)
Frequency band	2.402 to 2.480 GHz
Channel spacing	2 MHz
BLE beaconing channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz)
TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)
Antenna	
Type	Integrated meandered planar inverted F-antenna (PIFA)
Gain	2 dB (max)
Radiation diagram	Omnidirectional
Power	
Power supply	Battery
Replaceable	Yes
Type	CR2477 (3V, lithium)
Model	Panasonic Industrial CR2477 (typical capacity 1000 mAh @ 25°C)
Sensors and interfaces	
Sensors	3-axis MEMS linear accelerometer
Interfaces	2x LEDs (yellow, red)
Mechanical specifications	
Material	ABS plastic
Color	White
Size	77 x 46 x 16 mm (including flanges)
Weight	27 gr
Fastening	Screws (max. M3.5), cable-ties
Opening	Back lid with four screws
Protection	IP67/NEMA6
Flammability	UL 94 HB
Environmental specifications	
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under 0°C)
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)
Certifications	
CE (RED), FCC	

BlueUp reserves the right to change product specifications at any time without prior notice.
Wirepas is a trademark of Wirepas Oy , iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc.,
Quuppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.