


TagX Quuppa

Quuppa Intelligent Locating System® asset tag

Data sheet



Quuppa

Key features

- Suitable for outdoor and industrial applications
- Based on Nordic nRF52832
- Firmware based on Quuppa libraries
- 3-axis accelerometer for motion detection
- IP67 enclosure
- Flanges for flexible fastening options
- Powered by replaceable CR2477 coin battery

Quuppa Specifications	
Quuppa Compatible: based on Quuppa libraries	
Full support of Quuppa Intelligent Locating System® functionalities: BLE and proprietary channels, back-channel communication, profile configuration, OTA FW update	
Configuration and diagnostics	QSP (Quuppa Site Planner), QPE (Quuppa Positioning Engine)
Advertising interval	0.1 to 10 secs (BLE channel) 0.01 to 10 secs (Quuppa proprietary channel)
Advertising channels	BLE (CH37 – 2.402 GHz) or Quuppa proprietary
Quuppa ID	MAC address or custom ID
Custom features	Advanced motion detection (intensity/duration, shock, free-fall, man-down) Back-channels commands for configuration and trigger notification

Device specifications	
Electrical specifications	
Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
MCU core	ARM Cortex-M4 32-bit CPU
Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA
Radio specifications	
Standard	Quuppa Intelligent Locating System®
Frequency band	2.401 to 2.481 GHz (Bluetooth LE 4.0 + Quuppa proprietary channels)
Channel spacing	2 MHz
TX power	-40, -20 to 4 dBm (with 4 dB steps)
RX sensitivity	-94 dBm



Antenna	
Type	Integrated meandered planar inverted F-antenna (PIFA)
Gain	2 dB (max)
Radiation diagram	Omnidirectional
Power	
Power supply	Battery
Replaceable	Yes
Type	CR2477 (3V, lithium)
Model	Panasonic Industrial CR2477 (typical capacity 1000 mAh @ 25°C)
Sensors and interfaces	
Sensors	3-axis MEMS linear accelerometer
Interfaces	2x LEDs (yellow, red)
Mechanical specifications	
Material	ABS plastic
Color	White
Size	77 x 46 x 16 mm (including flanges)
Weight	27 gr
Fastening	Screws (max. M3.5), cable-ties
Opening	Back lid with four screws
Protection	IP67/NEMA6
Flammability	UL 94 HB
Environmental specifications	
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under 0°C)
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)
Certifications	
CE	

BlueUp reserves the right to change product specifications at any time without prior notice.
Quuppa and Quuppa Intelligent Locating System are trademarks of Quuppa Oy,
Bluetooth is a trademark of Bluetooth SIG, ARM and Cortex are trademarks of ARM Inc.