


## TagX LED Wirepas


Wirepas Mesh 2.4GHz asset tag with high-visibility LEDs

### Data sheet



#### Key features

- Suitable for outdoor and industrial applications
- Based on Nordic nRF52832
- Firmware based on Wirepas libraries
- 3-axis accelerometer for motion detection
- 2x high-visibility LEDs
- IP67 enclosure with flanges for flexible fastening
- Powered by replaceable CR2477 lithium battery


**Wirepas**

Wirepas Specifications	
Based on Wirepas Mesh 2.4GHz stack v5.x	
Available applications: Wirepas PosApp, BlueUp PosApp	
Wirepas PosApp	
Configuration and diagnostics	WNT (Wirepas Network Tool)
Operating modes	Opportunistic anchor, NRLS tag, Autoscan tag, DA tag
BLE beaconing	iBeacon, Eddystone UID, Eddystone URL (fixed packet)
BlueUp PosApp	
Configuration and diagnostics	WNT (Wirepas Network Tool) / BlueUp MeshCube
Operating modes	NRLS tag, Autoscan tag (configurable for each state)
Tag states	Default, Motion, Alarm, Sleep
Positioning interval and timeout	15 secs to 18 hours (configurable for each state)
BLE beaconing	iBeacon, Eddystone UID, Quuppa Emulation (configurable for each state)

Device specifications	
Electrical specifications	
Core module	Nordic nRF52832 SoC (MCU and radio transceiver)
MCU core	ARM Cortex-M4 32-bit CPU
Current consumption (25°C)	Radio TX: 7.1 mA (0 dBm TX) Radio RX: 6.5 mA Idle mode: 3 µA Idle mode with accelerometer ON: 7 µA



<b>Radio specifications</b>	
Standard	Wirepas Mesh 2.4GHz (stack v5.x)
Frequency band	2.402 to 2.480 GHz
Channel spacing	2 MHz
BLE beaconing channels	CH37 (2.402 GHz), CH38 (2.426 GHz), CH39 (2.480 GHz)
TX power	Conducted: +4 dBm (max) EIRP (Equivalent Isotropic Radiated Power): +6 dBm (max)
<b>Antenna</b>	
Type	Integrated meandered planar inverted F-antenna (PIFA)
Gain	2 dB (max)
Radiation diagram	Omnidirectional
<b>Power</b>	
Power supply	Battery
Replaceable	Yes
Type	CR2477 (3V, lithium)
Model	Panasonic Industrial CR2477 (typical capacity 1000 mAh @ 25°C)
<b>Sensors and interfaces</b>	
Sensors	3-axis MEMS linear accelerometer
Interfaces	2x high-visibility LEDs (yellow, red)
<b>Mechanical specifications</b>	
Material	ABS plastic
Color	White
Size	77 x 46 x 16 mm (including flanges)
Weight	27 gr
Fastening	Screws (max. M3.5), cable-ties
Opening	Back lid with four screws
Protection	IP67/NEMA6
Flammability	UL 94 HB
<b>Environmental specifications</b>	
Operating temperature	-20°C to +60°C (battery operating life sharply decreases under 0°C)
Storage temperature	+10°C to +30°C (with battery), -40°C to +85°C (without battery)
<b>Certifications</b>	
CE	

BlueUp reserves the right to change product specifications at any time without prior notice.  
Wirepas is a trademark of Wirepas Oy, iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc.,  
Quuppa is a trademark of Quuppa Oy, ARM and Cortex are trademarks of ARM Inc.